



26RK

Specifications

LOA LOD LWL	28'5" 25'5" 24'8"
Beam	8'4"
Mast Height	33'0"
Draft Range	15"-6'
Displacement	3,800 lbs
Towing Weight	6,000 lbs
Ballast	1,200 lbs
Sail Area	280 sq ft
Fuel Water Waste	7 gal 20 gal 20 gal

Standard Equipment

Electric Vertically Retracting Keel/Solid Lead Torpedo	Two-Line Stainless Rope Clutch
Vertically Retracting Rudder	Genoa Tracks and Blocks
Fully Battened, Full-Roached Mainsail with Reef Points	US Coast Guard Safety Kit
95% Foretriangle, Self-Tacking Jib	Private Head Compartment
Internal Halyards and Outhauls	Teak and Holly Sole in Main Cabin
Mast Light	Diamond Pattern Non-Skid Surfaces on Deck

Molded Flag Blue Gelcoat Sheer	Molded Structural Headliner
Bootstripe Flag Blue	Electric Circuit Breaker Panel
Laminated Wood tiller	12 Volt Cabin Lights
Iso-NPG Gelcoat/Vinylester Backup Below WL	20 Gallon Fresh Water Supply
Heavy Anodized Aluminum Strike Rail	Galley Sink
Outboard Motor Bracket (with non-diesel)	Galley Ice Box
Bowsprit with Anchor Roller	Cups and Plates in Recessed Holder
Running Lights	Swing Up/Down Dinette Table
Bow Pulpit with Lifelines	Stainless Steel Opening Ports with Screens (8)
Walk-Through Transom	Sunbrella Fabric on Interior Cushions
Stainless Cleats (3), Four Bolt Styles	Fabric Curtains for Privacy in Head and V-Berth
Stainless Steel Deck Hatch (1)	Open Interior Layout (no interior bulkhead except head compartment side walls)
Andersen Winches - 2 sheet, 1 Halyard (all #10)	Stainless Gunnel Trim