




JEANNEAU SUN ODYSSEY 455

SPECIFICATIONS

Overall length	14,28 m	46'9"
Overall Length with bowsprit	14,78 m	48'5"
Hull length	13,74 m	45'1"
Waterline length	13,58 m	44'5"
Beam	4,49 m	14'8"
Displacement light load with deep draft keel	11 230 kg	24 758 lbs
Standard keel draft	2,35 m	7'7"
Standard keel weight	2 691 kg	5 933 lbs
Shoal keel draft	1,75 m	5'7"
Shoal keel weight	3 050 kg	6 724 lbs

Fuel capacity	190 L	50 US gal
Water capacity	380 L	100 US gal
Fridge capacity	190 L	50 US gal
Holding tank capacity	144 L	38 US gal
Standard mainsail, horizontally-cut, in High Strength polyester	54 m ²	581 Sq ft
Standard 120 % genoa, horizontally-cut, in High Strength polyester	49 m ²	527 Sq ft
CE category	A10 / B11 / C12	
Architect / Designer	Marc Lombard Yacht Design Piaton Yacht Design Jeanneau Design	



AN EXCEPTIONAL LEVEL OF EQUIPMENT

EXTERIOR

Sailing features

- High aspect ratio rig, cathedral mast and split rigging
- Harken® roof and primary winches
- Harken® deck hardware
- Anodised aluminium mast and boom
- Boom with rigid boom vang and lowered gooseneck, to ease manoeuvring
- Semi-battened mainsail and furling genoa with UV protection
- Discontinuous standing rigging, stainless steel wire
- Lazy bag and lazy jacks
- Sheets lead back to the helm - German sheeting
- Large choice of sails sets

Construction

- Infused monolithic hull, fibreglass and polyester resins, ISO gelcoat surface, protective barrier coat
- Infused fiberglass inner liner, relamination in stays attachment areas.
- Injected deck
- Twin rudders with self-aligning roller bearings and textile lines, to increase control and pleasure in navigation

Cockpit

- Walk-in access to side decks, enabling to walk around the deck without crossing any steps
- 2 fixed cockpit tables
- Leather-covered stainless steel steering wheels

- Large aft fold-down swim platform with telescopic ladder
- Telescopic bath ladder
- Hinged companionway doors

Deck

- Flush deck hatches
- Long tinted acrylic roof windows
- Split rigging: Inboard shrouds for easier access forward
- External woodwork and inlays made of wood
- Mid-ship cleats
- Electric windlass Lofrans
- Taquets d'amarrage aluminium au maître-bau
- Guindeau électrique Lofrans

INTERIOR

- One-level interior with no door sills for cabins
- Large doors, double access to aft head
- Leather-wrapped handrails
- LED lighting
- Large double berths
- Fully-upholstered hull sides
- Blinds for each hatch and opening in the forward and aft cabins
- Numerous choices of interior ambiances
- Large seaworthy storage spaces, with fiddles, soft closing drawers and cabinets
- Separated shower compartment in the forward owner's cabin

Chart table (Version A)

- Charts table with opening top, laptop compartment, open storage space, large fold-away seat for sitting or lying down, electrical panel, reading light and bookcase

Workshop (Version A)

- Enclosed and ventilated starboard storage compartment, with shelving, removable storage bins, a hanging locker, or space for an optional refrigerator or a pre-fitting for a washing machine.

Galley

- U-shape galley, ideally located near the centre of gravity of the boat
- Compact counter top
- Double stainless steel sinks with covers
- 2-burner stove with oven
- Fridge 190 L / 50 US gal with top and front access

TECHNICAL

Electrical

- LED navigation and anchoring lights
- 12 V electrical panel
- Battery Exide Dual Marine
- 125 Ah alternator and charge distributor/isolator
- Positive and negative battery cut-off switches to better protect battery banks

Water System

- Hot and cold cockpit shower
- Hot water heater 40 L / 11 US gal
- "Heavy-duty" water pump

Engine

- Latest-generation Yanmar Common Rail Sail Drive engine
- Fixed 3-blade propeller
- Sound insulation 1½" thick, with fire retardant film

TRIM LEVELS AND PACKS

I TRIM LEVEL

	"PREMIERE"	"PREFERENCE"
GRP bowsprit with integrated anchor roller (replaces the standard anchor roller)	•	•
Helm consoles port side and starboard side	•	•
Second windlass control with chain counter, installed in the cockpit	•	•
Lifeline	•	•
Halyard bags in the cockpit and on the roof (4)	•	•
2x 40 Ah battery chargers for 12 V battery banks	•	•
3x 95 Ah additional service batteries	•	•
LED courtesy lighting in the cockpit	•	•
3 burner cooker and oven with grill function (replaces standard 2 burner cooker)	•	•
Counter top in Corian®, with fiddles	•	•
Navicolor battery monitoring	•	•
Indirect LED lighting in the saloon		•
Shades for windows and ports in the saloon		•
Shades and screens for hatches in the saloon		•
Signature clock and barometer set at the chart table		•
Upholstered headboard in the owner's cabin in Maglia Artica fabric		•

EXTERIOR AND TECHNICAL EQUIPMENT

I ARCHITECTURE

- Full-length hull chine for improved stability and speed
- Long waterline for better speed while sailing and under power
- L-shaped cast iron keel
- Twin rudders with self-aligning roller bearings and textile lines, to increase control and pleasure in navigation

I SAILS

Standard

- Horizontally-cut in High Strength polyester
- Semi-battened main sail with 3 reefs 54 m² / 581 Sq ft
- Génois enrouleur 120 % avec bande anti-UV 49 m² / 527 Sq ft

Options

- In mast furling main sail horizontally-cut in High Strength polyester 46,1 m² / 496 Sq ft
- Self-tacking jib with UV protection in High Strength polyester 39 m² / 420 Sq ft
- Code 0 in triradial cross cut Mylar/Aramid laminate 85,74 m² / 923 Sq ft with continuous line furler (requires Downwind pack)
- Asymmetrical spinnaker on socket 178 m² / 1 916 Sq ft

I SAIL HANDLING

Standard

- Mainsheet attached to Dyneema® bridle forward of companionway, with sheets led back to the cockpit winches
- 3D system for genoa sheets
- Spinlock® jammers
- Coachroof winch 1 x Harken® 46.2 ST on port side
- Genoa winches 2 x Harken® 50.2 ST winches for easy use at the helm stations
- Harken® winch handle

Options

- Self-tacking jib ball bearing track on coachroof
- Electrical coachroof winch Harken® 46.2 ST on port side
- 2 x electrical primary winches Harken® 50.2 ST

I MAST AND RIGGING

Standard

- Classic aluminium mast with double spreaders, deck-stepped, cathedral geometry and split rigging
- Aluminium boom with rigid vang and lowered goose neck for easier handling
- Double backstay
- Genoa furler with double slot, furling line lead aft to cockpit on coach roof
- Running rigging topping lift, mainsail halyard, genoa halyard, mainsheet, genoa sheets in polyester
- Standing rigging discontinuous 1 x 19 stainless steel wire
- Asymmetrical lazy bag with integrated lazy jacks

Option

- Furling mast aluminium with double spreaders, deck-stepped, cathedral geometry and split rigging

I COCKPIT

Standard

- Walk-in access to side decks, enabling to walk around the deck without crossing any steps.
- 2 fixed cockpit tables in polyester with handrails and cup holders
- Wooden inlay on bench seats, helms stations and transom platform
- Fixed coaming with ideal height for comfort and safety
- 2 Cockpit lockers in the center
- 2 cockpit lockers under the seats on both side
- Universal gas box, cut-off valve under the stove
- Steering wheels with leather wrap
- Emergency tiller, and fitting in cockpit floor
- Engine control: throttle lever at starboard helmstation and engine panel
- Large bathing platform with telescopic ladder, handrail and access step to the cockpit
- Hinged companionway doors in plexiglass
- Sliding horizontal hatch in plexiglass
- Cockpit tables in polyester, fixed legs, handrails and cup holders

Options

- Telescopic cockpit tables
- Wooden cockpit tables
- Wooden inlay on cockpit floor
- Large cockpit sprayhood in T-TOP®, high transparency windscreen and LED cockpit lighting
- Cockpit Bimini with stainless steel bows in T-TOP®, connecting fabric between Bimini and sprayhood
- Cockpit enclosure kit in T-TOP®, fitted on the sprayhood and bimini
- Electrical bathing platform system with remote

I DECK HARDWARE

Standard

- Bow pulpit in stainless steel
- Stern pushpits in stainless steel with buoy bracket and emergency ladder
- Double level of stainless steel lifelines
- 6 aluminium mooring cleats
- Stainless steel handrails on coachroof (2)
- Deep anchor locker
- Electric 12 V Lofrans windlass 1 000 W - 10 mm chain
- Long fixed tinted windows along coach roof
- Fixed cockpit windows in the aft cabins (2)
- Large, fixed hull ports (6)
- Opening ports in the roof (3)
- Opening deck flush hatches (8)
- Opening ports towards cockpit in the aft cabins (1 per cabin)
- Opening ports towards side-deck in the aft cabins (1 per cabin)

Options

- Wooden side-decks
- Rubrail for hull protection
- Mooring kit 6 fenders and 4 docklines
- Anchoring kit with Delta 20 kg / 44 lbs, 32 m / 104'11" of 10 mm chain and 45 m / 147'7" line
- Sunbed on the foredeck

DOWNWIND PACK

- Spinnaker rigging with Spinlock® jammers
- Halyards and sheet for asymmetrical spinnaker / Code 0 (2 polyester halyards, 1 sheet and 1 tack line in Dyneema®, pulleys on mast step and side decks)
- Extra Harken® 46.2 ST winch on starboard on coachroof
- Extra winch handle
- Windex 15" on mast head

PERFORMANCE PACK

- Downwind pack
- Performance full-batten mainsail, triradial cut, in DCX® grey 55 m² / 591 Sq ft
- 120 % performance genoa, triradial cut, in DCX® grey with UV protection 49,8 m² / 536 Sq ft
- Dyneema® low-stretch halyards and sheets for main and genoa
- Hydraulic textile adjustable backstay
- Flat-deck genoa furler

PACK ENTERTAINMENT AUDIO

- Fusion® APOLLO RA670 player (Radio / USB / Bluetooth...)
- PIONEER® speakers in the saloon
- Fusion® speakers in the cockpit

I SAIL LOCKER

Standard

- Access via lockable deck hatch
- Access ladder in stainless steel

I LIGHTING

Standard

- Full LED interior lighting

I ELECTRICAL

Standard

- Main 12 V electrical panel at the chart table
- 12V Circuit for house and engine system
- Domestic battery bank capacity 2 x 95 Ah / 12 V
- Engine start battery capacity 1 x 50 Ah / 12 V
- 12 V engine alternator: 125 Ah
- Positive and negative battery switch 12 V in the aft cabin

Options

- USB plug in each cabin
- Inverter 12 V > 220 V 2 000 W enable to use 220 V appliance from the domestic battery bank
- Generator Onan 7,5 KW 230V 2 400 rpm

I PLUMBING

Standard

FRESH WATER

- Pressurised water distributed through-out the boat via semi-rigid hose
- "Heavy-duty" water pump 19 L / 5 US gal / mn, accumulator tank for consistent water pressure
- Water tank: 380 L / 100 US gal, under the forward cabin berth
- Tank gauges (1 per tank)
- Water boiler 40 L / 11 US gal connected to the engine and 220 V circuit
- Hot and cold cockpit shower on transom

Option

- Additional water tank: 200 L / 53 US gal, under the aft cabin berth on starboard side

GREY AND BLACK WATER

- Automatic electrical shower self-activating
- Large bowl marine toilets
- Black water tank 80 L / 21 US gal for forward cabin, 64 L / 17 US gal for aft head (VERSION A)
- Black water tank 64 L / 17 US gal in heads (VERSIONS B and C)

BILGES DRAINAGE

- Electric bilge pump located in bilge area with activation via switch at electrical panel
- Dual-action manual bilge pump located in the cockpit, with separate hose from primary bilge pump

GAS

- Gas leakage detector

Options

- Electric Quiet-Flush toilets, on fresh water circuit, in place of manual toilets
- Water intake in the cockpit. Enable to connect the fresh water circuit directly to the shore

I ENGINE

Standard

- Latest-generation Common Rail engine with reduced emissions and consumption
- Yanmar Engine 4JH57CR Sail Drive - 57 HP / 42 kW - Alternator 125 Ah
- Engine panel and throttle located at the starboard helm station
- Insulation: Foam 40 mm, with fire retardant film
- Built-in muffler, air ventilation and stainless steel exhaust fitting
- Fixed 3 blade propeller
- Ventilation system extractor fan located near the engine, benefiting from the insulation of the engine room. Outlets vents at the back of cockpit
- Roto moulded fuel tank 190 L / 50 US gal located under the aft cabin berth, fuel / water separator
- Access behind steps to engine compartment and from aft cabins

Options

- Yanmar Engine 4JH80CR Sail Drive - 80 HP / 59 kW - Alternator 125 Ah, includes the electrical engine throttle
- Extra fuel tank 200 L / 53 US gal, instead of a fresh water tank underneath the aft cabin berth
- Tunnel bow thruster Side Power SE100/185T - power 8.4 hp - thrust 116 kg - 24V
- Flex-o-fold 3 blade folding propeller

INTERIOR EQUIPMENT AND LAYOUTS



Version A
Forward master cabin,
2 aft cabins / 2 heads



Version B
2 forward cabins,
2 aft cabins / 4 heads



Version C
2 forward cabins,
3 aft cabins / 3 heads

WOODWORK

Standard

- Teck interior woodwork laminated with solid wood trim, UV stabilized varnish
- Fully-upholstered hull sides and ceiling
- Lindberg laminated oak floorboard

Options

- Woodwork in Alpi® grey Cedar mat finish (VERSION A)
- Charter woodwork in laminated wood Laos Teck (VERSIONS B et C)
- Dark Oak laminate floorboards (VERSION A)

SALOON

Standard

- Comfortable seating arrangement to port side with view of sea through hull ports
- Hinged storage compartments under settee
- Large storage behind backrests
- Large table with 2 removable aluminium legs
- Companionway with anti-sleep floor surface

Options

- Convertible berth in saloon
- Saloon table "Luxe" in 2 parts, on telescopic legs, 1 part can be up while the other one is down

CHART TABLE (version A)

- Large chart table, opening compartment for laptop computer, electronic panel, USB plug
- Large removable charts table seat, chaise longue style, with storage underneath
- Multiple storage for telephone, keys...
- Large storage space under electrical panel for books and other navigation equipment, storage underneath the seat
- Ergonomic seat, seaworthy

WORKSHOP (version A)

Standard

- Large workshop on starboard side, closed
- Storage shelf with hanging rail, removable plastic bins (6), bottle rack and shelves
- Hull window for natural light and opening porthole for ventilation

Options

- Additional 65L / 17 US gal refrigerator
- Pre-fitting for washer-dryer

GALLEY

Standard

- U-shaped galley located on starboard side, with view on the sea
- Double stainless steel sinks with chrome fixtures
- Soft-close, fully-extending drawers
- 2 waste bins for recycling, located under the sink
- Open storage behind the galley
- 2 burners stove with protective handrail
- Fridge 190 L / 50 US gal with top opening and front opening
- Closed storage under the countertop with 220V socket
- Bottle storage, compartmentalised, under the countertop
- Spice drawer, to the right of the oven (VERSION A)
- Large storage, to the right of the oven (VERSIONS B and C)
- Top storages along the entire length of the galley

Options

- Pre-fitting for Microwave
- Additional drawer fridge in the galley (VERSIONS B et C)

COMFORT

Standard

- Cushions in High Density foam 120 mm in the salon
- High Density Premium mattresses in cabins

Options

- Air conditioning working from generator or shore power with 3 units (32 000 BTU in total)
- Pushed air heating system 5 500 W with outlets in each cabin and head (VERSION A)
- Pushed air heating system 11 000 W with outlets in each cabin and head (VERSION B and C)

FORWARD OWNER'S CABIN (version A)

Standard

- Island bed 2,00 x 1,60 m / 6'6" x 5'2"
- Large wardrobe on the starboard side with deep hanging space and high shelves
- Biblioteca integrada en el mueble vestidor a estribor
- 2 large drawers underneath the berth
- Side bed tables with leatherette
- Fully upholstered front bulkhead
- LED lighting
- 2 opening deck hatches above the bed, and 2 small ones in the passageway
- 2 large fixed hull ports with sliding blinds
- Deck hatches with blind and bug screens
- Front owner's head: GRP sink furniture, mirror above the sink with direct lighting, drawers under the sink, opened storage shelves with edges, hull port allowing sea view, opening deck hatch, 2 ceiling spotlights. Separated shower, with its dedicated opening deck hatch and plexiglass door, shower, shower drain with automatic switch

Options

- Mattress battens
- Electric Quiet-Flush toilets, on fresh water circuit, in place of manual toilets

AFT CABIN(S)

- Large berth 2,00m x 1,50m-1,15m / 6'6" x 4'9"-3'8"
- Hanging locker storage and shelf along hull
- LED Lighting
- LED reading lights
- 1 long fixed hull port, 1 large fixed cockpit window
- 1 cockpit opening porthole, 1 side deck opening porthole
- Blinds for each opening
- Access to tanks and technical area behind the engine
- Starboard aft head: double access, from starboard cabin and saloon, GRP sink furniture, storages, high shelves with edges, large roof window, opening port for light and ventilation, 2 ceiling spotlights, separated shower, shower drain with automatic switch, water inlet valve and connector underneath the sink, large marine toilet with manual pump, hook, large mirror, shower separated with a plexiglass door on versions A and B

PORT SIDE HEAD (version A)

- Port side aft head: double access, from aft port side cabin and saloon, GRP sink furniture, storages, large roof window, opening port for light and ventilation, 2 ceiling spotlights, shower, shower drain, water inlet valve and connector underneath the sink, large marine toilet with manual pump, hook, large mirror, shower separated with a plexiglass door.

PORT SIDE LATERAL CABIN (versions C)

- 2 bunk beds, hanging locker, reading light
- Opening deck hatch for ventilation, fixed roof windows

WORKSHOP (VERSION B)

- Large storage on portside
- Shelf
- Clothes rail
- Additional storage at the bottom

TWIN FORWARD CABINS (versions B and C)

- Large rectangular berth 2,00 x 1,35/0,78 m / 6'6" x 4'4"/2'6"
- Hanging locker
- Storage above the berth
- LED lighting
- Opening deck hatch with ventilation
- Large fixed hull windows with sliding blinds
- Blinds and bugs screens for deck hatches
- Forward heads: GRP sink furniture, storage, hull port allowing sea view, opening deck hatch for light and ventilation, 1 ceiling spotlight, shower, shower drain, water inlet valve and connector underneath the sink, large marine toilet with manual pump, hook



MARINE SERVICENTER

San Diego Marina del Rey Seattle Bellingham
 619.733.0559 310.963.3750 206.323.2405 360.770.0180
 info@marinesc.com marinesc.com

